



Product Datasheet

06 Downlights Fixed LED>The IP54 Bathroom Downlights

10107B/W/W



7W LED recessed downlight, IP54. Suitable for bathroom installations.

Supplied with non-dimmable LED 180mA driver.

Complies with standard EN60598-1 and any other specific standards.











Downloads










Dimensions



80mm



45mm

Gallery







Physical Specification

Item Group	
Family	
Order Code	
Colour	
Material	
Diffuser Material	
Shape	

06 Downlights Fixed LED

The IP54 Bathroom Downlights

10107B/W/W

White

Die Cast

Plastic

Circular

Height	45mm
Diameter	80mm
Cutout Hole Diameter	65mm
Recessed Ceiling	Yes
Depth Required	70mm
Indoor	Yes
Outdoor	Yes
Adjustable	No
Electrical Characteristics	
Gear	External-Included
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	7W
IP Rating	IP54
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	180mA
Voltage	35V
Safety Class	ŢIII>
Power(Watts)	6,3W
IP Rating	IP54
Light Source	LED built in

LED Type	SMD 2835
LED Brand	Epistar
LED Number	14
F Mark	F
Gear	
Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	5,4-7,2W
Power Factor	0,9
Constant Current	Yes
Output	180mA
Voltage Range	30-40V
IP Rating	IP20
Safety Class	
Dimmable	No
Ambient Temp	45°C
Operating Temp	70°C
Housing Material	Plastic
Output Terminal	Cable
Brand	0
Protection	Short Circuit and Overload
llumination Data	
Colour Temperature	3000K
Lumen Output	500lm
Light Efficiency	71,42lm/W
CRI	80
Beam Angle	90°



Packing Info

Box Length	10cm
Box Width	10cm
Box Height	9cm
Box Weight	0.228kg
Pcs/Carton	50
Barcode	5291889043188
HS Code	9405413990

Certification & Warranty

Warranty	2 Years
Average Lifetime	40000hrs
Weee Directive	Yes

switch to one light!

