

10 Office & Kitchen>UGR19 Backlit CCT V

62140BRU/W/V



30x120cm adjustable CCT surface mounted backlit LED panel with microprismatic diffuser.

Uniform lighting, ideal for commercial applications.

Complete with 1000mA driver.

Complies with standard EN60598-1 and any other specific standards.

↪ ↑ IP20 80 CRI UGR19  

Downloads



Dimensions



Physical Specification

Item Group	10 Office & Kitchen
Family	UGR19 Backlit CCT V
Order Code	62140BRU/W/V
Colour	White
Material	Aluminium + Steel
Shape	Rectangular
Length	1200mm
Width	300mm
Height	42mm
Surface Ceiling	Yes
Indoor	Yes
Adjustable	No

Electrical Characteristics

Gear

Built In

Fitting + Driver

Input Voltage

220-240V

50 Hz

Yes

60 Hz

Yes

Safety Class

Power(Watts)

40W

IP Rating

IP20

Light Source

LED built in

Dimmable

No

F Mark



Fitting

Input Type

Constant Current

Input Current

1000mA

Voltage

38V

Power(Watts)

38W

IP Rating

IP20

Light Source

LED built in

LED Type

SMD 2835

LED Brand

Sanan

F Mark



Gear

Gear Type

Led Driver

Input Voltage

220-240V

50 Hz

Yes

60 Hz

Yes

Power(Watts)

25W-38W

Constant Current

1000mA

IP Rating

Dimmable

Housing Material

Yes

25V-38V

IP20

No

Plastic

Illumination Data

Colour Temperature

3000K-4000K-5700K

Lumen Output

3600lm-4000lm-3800lm

Light Efficiency

90lm/W - 100lm/W - 95Lm/W

CRI

80



Illumination Diagram

19

UGR

Packing Info

Box Weight

2.950kg

Pcs/Carton

4

Barcode

5291889077183

HS Code

9405413990

Certification & Warranty

Warranty

3 years

Weee Directive

Yes

switch to
one light!

