



LED Floor Standing Panel Light PT Series (UGR<16)













• **Up Lighting** (50%-40W)



Down Lighting (50%-40W)




• Features:

- » PMMALGP
- » CRI>90Ra/95Ra
- >> 110~120lm/w
- >> Flicker-free driver
- >> Lower Glare: UGR<16</p>
- Up and Down Lighting
- >> With 1-10V Dimming
- With PIR Motion Sensor & Daylight Sensor
- » CCT Adjustable(3000K~6000K)



About PIR Motion Sensor & Daylight Sensor



- » IP65 sensor housing design
- >> With remote controller setting, easy to enable and disable the motion sensor.
- » Lux sensor build in to detect the ambient lux and lux level adjustable.
- » Detection Angle: 120°
- >> Hold time: 5s/1min/3min/10min
- » Sensitivity: 100%/75%/50%/25%
- >> Stand-by period: 0s/10s/10min/+∞
- Daylight threshold: Disable/10Lux/25Lux/50Lux


Touch Panel Controller




Color: White, Black



Explosion Drawing



Dimmension(cm)



Parameter


Power	80W
Luminous Efficiency	>110 lm/W
Height	198cm
Input Voltage	AC220~240V
Power factor (P-F.)	>0.95
LED source	LUMILEDS2835, CRI> 90Ra/95Ra
Color Temprature	3000~6000K
Index of protection	IP40
Beam angle	120°
Material	Aluminum+PMMA
Working temperature	-20°C~+50°C
Lifetime	>50000 hrs
Warranty time	5 y ears
Certification	CE,RoHS


Product packaging

When calculating freight and volume of cartons, each side shall be increased by 2~3cm (according to the calculation method of freight forwardeer).

Content	Dimmension	Weight(N.W)
Panel frame+Base	75.3x36.3x15.2cm	16.55KG
Floor Pole	194.1x11.2x11.5cm	

Base / Panel frame / Die-casting head/gland cover / Sensor remote / Accessories / Instruction for installation





Shipping Carton

Caution

- 1. In case of electric shock, please make sure the power is off before installation.
- 2. The lamp should be installed and operated by a qualified electrician or technician in accordance with relevant local codes.
- 3. Do not use sharp tools near or on the surface of the lamp.
- 4. Unpack and examine the product carefully. Report any damage and save all packing materials if any portion of the product was damaged during transportation.

Statement

- 1. It is only allowed to be used in indoor environments, OLAMLED promises a full warranty for the product.
- 2. Can not be used in any harsh environment, including high/low temperature, high humidity, high salinity, high ammonia, etc.
- 3. The warranty policy is no longer warranted in the event of any incorrect application



Table installation



Application scenario

- » Business Office
- » Public Library
- » Reading Room





