



# Flexaglow

SOS-RS-1010-24V08-2835T-160D



## Key Information

|            |                                     |       |       |
|------------|-------------------------------------|-------|-------|
| Dimensions | 10 x 10 mm<br>Fourni en 5/10 ou 20M | Power | 15W/m |
|------------|-------------------------------------|-------|-------|

|                |             |
|----------------|-------------|
| Luminaire type | Strip light |
|----------------|-------------|

|               |                 |
|---------------|-----------------|
| Mounting type | Track / Profile |
|---------------|-----------------|

## DATA SHEET

|                              |                              |
|------------------------------|------------------------------|
| Compliance certificates      | CE, ROHS, SAA                |
| Colours                      | -                            |
| Light source type            | LED                          |
| Construction material        | Silicone                     |
| Protection rating (IP)       | IP67                         |
| Protection class             | -                            |
| Impact resistance            | -                            |
| Operating temperature        | -20°C ~45°C                  |
| Cutout                       | -                            |
| Luminous efficacy (lm/W)     | 40-114lm/W                   |
| Luminaire lumens (lm)        | 363-1134lm/m                 |
| LED lifepsan                 | 50,000 hours                 |
| Colour Rendering Index (CRI) | >90Ra                        |
| Colour temperature (K)       | 2700/3000/4000/5700 or 6500K |
| Dimming                      | According to driver          |
| Smart / Connected luminaire  | No                           |
| Beam angle (°)               | -                            |
| MACADAM                      | -                            |
| LED Type (SMD, COB)          | -                            |
| RGB capability               | Oui                          |
| UGR                          | -                            |
| Supply voltage (V)           | AC200-240V                   |



## Flexaglow

SOS-RS-1010-24V08-2835T-160D

### Application

