



## **Product Datasheet**

New 2025 Edition 2>Downlights Fixed LED

### 10107B/W/V



7W LED CCT Variable recessed downlight, IP54. Suitable for bathroom installations.

Complete with non-dimmable driver.

Complies with standard EN60598-1 and any other specific standards.













#### Downloads









#### Dimensions



80mm



45mm

#### Gallery







#### **Physical Specification**

Item Group	
Family	
Order Code	
Colour	
Material	
Diffuser Material	
Shape	

#### New 2025 Edition 2

Downlights Fixed LED

10107B/W/V

White

Die Cast

Plastic

Circular

Height	45mm
Diameter	80mm
Cutout Hole Diameter	65mm
Recessed Ceiling	Yes
Depth Required	70mm
Indoor	Yes
Outdoor	Yes
Adjustable	No
Electrical Characteristics	
Gear	External-Included
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	7W
IP Rating	IP54
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	160mA
Safety Class	
IP Rating	IP54
Light Source	LED built in
LED Type	SMD 2835

F Mark	F
Gear	
Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Constant Current	Yes
IP Rating	IP20
Safety Class	
Dimmable	No
Brand	0
umination Data	
umination Data  Colour Temperature	3000K-4000K-5000K
Colour Temperature  Lumen Output	3000K-4000K-5000K 540lm
Colour Temperature	
Colour Temperature  Lumen Output	540lm
Colour Temperature  Lumen Output  Light Efficiency	540lm 77lm/VV
Colour Temperature  Lumen Output  Light Efficiency  CRI	540lm 77lm/W 80
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle	540lm 77lm/W 80 90°
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle	540lm 77lm/VV 80 90°
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram	540lm 77lm/W 80 90°
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram	540lm 77lm/W 80 90°
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram	540lm  77lm/VV  80  90°
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram  acking Info  Box Weight	540lm  77lm/W  80  90°  1  0.244kg

#### Certification & Warranty

# switch to one light!

