



12 Wall & Ceiling LED>The Opal Diffuser Cylinders CCT V

12114M/W/V



14W CCT Variable LED surface mounted downlight.

Complete with non-dimmable driver.


Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Physical Specification

Item Group	12 Wall & Ceiling LED
Family	The Opal Diffuser Cylinders CCT V
Order Code	12114M/W/V
Colour	White
Material	Aluminium
Shape	Circular
Height	65mm
Diameter	118mm
Surface Ceiling	Yes
Indoor	Yes
Adjustable	No

Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	14W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	

Fitting	
Input Type	Constant Current
Input Current	350mA
Light Source	LED built in
LED Type	SMD

Gear	
Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Output	350mA
Dimmable	No

Illumination Data

Colour Temperature	3000K-4000K-5000K
Lumen Output	1120lm

Light Efficiency
CRI
Beam Angle
Illumination Diagram

80lm/W

90

120°



Packing Info

Box Weight
Pcs/Carton
Barcode
HS Code

0.450kg

30

5291889085430

9405413990

Certification & Warranty

Warranty

3 years

switch to
one light!

one
LIGHT

